

CME Truck Mounted Drills								
	45B	45C	55	55LC	55LCX	75	85	95
Standard Rotary Box								
Rotational Speed (max)	760 rpm	760 rpm	800 rpm	800 rpm	600 rpm	740 rpm	490 rpm	540 rpm
Rotary Torque (max)	3,530 ft/lbs (4,785 Nm)	3,530 ft/lbs (4,785 Nm)	7,780 ft/lbs (10,545 Nm)	7,780 ft/lbs (10,545 Nm)	11,950 ft/lbs (16,200 Nm)	10,440 ft/lbs (14,150 Nm)	22,950 ft/lbs (31,115 Nm)	30,200 ft/lbs (40,945 Nm)
High Torque Rotary Box								
Rotational Speed (max)	550 rpm	550 rpm	665 rpm	665 rpm	N/A	585 rpm	N/A	450 rpm
Rotary Torque (max)	4,850 ft/lbs (6,575 Nm)	4,850 ft/lbs (6,575 Nm)	9,425 ft/lbs (12,775 Nm)	9,425 ft/lbs (12,775 Nm)	N/A	13,225 ft/lbs (17,930 Nm)	N/A	36,100 ft/lbs (48,945 Nm)
High Speed Rotary Box								
Rotational Speed (max)	N/A	N/A	N/A	N/A	N/A	930 rpm	620 rpm	N/A
Rotary Torque (max)	N/A	N/A	N/A	N/A	N/A	8,355 ft/lbs (11,325 Nm)	18,080 ft/lbs (24,510 Nm)	N/A
Feed System								
Pull Down Force	13,650 lbs (6,190 kg)	13,650 lbs (6,190 kg)	18,650 lbs (8,460 kg)	19,750 lbs (8,959 kg)	19,750 lbs (8,959 kg)	20,000 lbs (9,070 kg)	28,225 lbs (12,800 kg)	33,135 lbs (15,030 kg)
Retract Force	19,600 lbs (8,890 kg)	19,600 lbs (8,890 kg)	28,275 lbs (12,825 kg)	27,615 lbs (12,526 kg)	27,615 lbs (12,526 kg)	30,000 lbs (13,600 kg)	48,100 lbs (21,815 kg)	62,830 lbs (28,500 kg)

Performance ratings are based on engineering specifications, calculations and accepted industry standards.

Capacities may vary according to drilling conditions. CME reserves the right to amend these specifications at any time, without notice.