

<b>CME Trailer Mounted Drills</b>					
	45B	45C	55	55LC	55LCX
<b>Standard Rotary Box</b>					
Rotational Speed (max)	760 rpm	760 rpm	800 rpm	800 rpm	600 rpm
Rotary Torque (max)	3,530 ft lbs (4,785 Nm)	3,530 ft lbs (4,785 Nm)	7,780 ft lbs (10,545 Nm)	7,780 ft lbs (10,545 Nm)	11,952 ft lbs (16,200 Nm)
<b>High Torque Rotary Box</b>					
Rotational Speed (max)	550 rpm	550 rpm	665 rpm	665 rpm	N/A
Rotary Torque (max)	4,850 ft lbs (6,575 Nm)	4,850 ft lbs (6,575 Nm)	9,425 ft lbs (12,775 Nm)	9,425 ft lbs (12,775 Nm)	N/A
<b>Feed System</b>					
Pull Down Force	13,650 lbs (6,190 kg)	13,650 lbs (6,190 kg)	18,650 lbs (8,460 kg)	19,750 lbs (8,959 kg)	19,750 lbs (8,959 kg)
Retract Force	19,600 lbs (8,890 kg)	19,600 lbs (8,890 kg)	28,275 lbs (12,825 kg)	27,615 lbs (12,526 kg)	27,615 lbs (12,526 kg)

*Performance ratings are based on engineering specifications, calculations and accepted industry standards.*

*Capacities may vary according to drilling conditions. CME reserves the right to amend these specifications at any time, without notice.*